

Zonet®

IP Camera ZVC7610



Features:

- Secure your home from anywhere via the Internet.
- Integrated web server – viewable from most web browsers
- Supports enhanced MPEG-4 and MJPEG compression
- View video you're your Wireless-G or wired Ethernet network
- Free Ultra-View
- Motion Detection and E-mail notification.
- Supports resolution of up to 640x480 pixels
- Multi-platform support—TCP/IP, SMTP (E-Mail), HTTP, DHCP
- Windows-based Setup Wizard for easy setup

The Zonet **ZVC7610 - IP Camera** delivers real-time, high quality video/image over the networks. The ZVC7610 functions as a video/surveillance camera allowing you to view live events with your web browser via Internet or Intranet. This compact, self-contained unit lets you keep track of your home, your kids, and your workplace -- whatever's important to you.

It delivers simultaneous MPEG-4 and Motion JPEG video, motion detect, night-shot mode, automatic image capture, and e-mail alerts, making it the ideal solution for Internet video broadcasting applications.

IP Camera

ZVC7610

Package content:

- One ZVC7610
- One AC Power Adapter
- One Camera Stand
- One RJ-45 Ethernet Cable
- One Installation CD w/ User Manual
- One Quick Installation Guide

Related Products:

ZVC7610W	Wireless IP Camera
ZVC7630	2-Way Audio IP Camera
ZVC7630W	Wireless 2-Way Audio IP Camera

Toll Free

1.888.883.8880

Zonet USA Corporation
19929 Harrison Ave,
Walnut, CA 91789
Tel: 909.594.3338
Fax: 909.594.3336
Email: sales@zonetusa.com
Web: www.zonetusa.com

Specification

Image Sensor

Sensor	1/4" Color CMOS Sensor
Resolution	640x480 pixel
Minimum Illumination	0.5 LUX
Lens	f: 4.6mm, F: 2.6 (Broad Lens)
View Angle	60° (Diagonal)

Video/Image

Video Format	MJPEG
Image Frame Rate	30 fps @ VGA, QVGA, QQVGA
Digital Zoom	3x
Image setting	Brightness, Sharpness, Saturation
Flip Images	Vertical/Horizontal

System

Processor	ARM9 base
ROM	4MByte NOR Flash
RAM	16MByte SDRAM

Mechanical/Environment

Power	DC5V
Power Consumption	Power Consumption
LEDs	Power (orange); Link/ACT (Green)
Environment	Operation: Temp: 0°C ~ 45°C Humidity: 20% ~ 85% non-condensing Storage: Temp: -15°C ~ 60°C Humidity: 0% ~ 90% non-condensing

Communication

Ethernet	One RJ45 port; IEEE 802.3u compliant 10/100 Mbps Fast Ethernet with Auto-MDIX
Protocols	TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, PPPoE, UPnP

Software

Supported OS	Windows 2000/XP/Vista
UltraView	View channel:16 CHs Record/Playback/Motion detect Backup/Restore to/from Configuration file
IP Finder	Auto search IP Address of Camera in LAN